

**Ceiling unit
Pureline Pro 120 cm
White**



EAN 5414425222148

Energy label

▪ Energy Efficiency class (EElhood)	A
▪ Annual Energy Consumption (kWh/year) (AEChood)	41,4
▪ Fluid Dynamic Efficiency class (FDEhood)	A
▪ Lighting Efficiency class (LEhood)	C
▪ Grease Filtering Efficiency class (GFEhood)	D

Functions & features

▪ Motor	Integrated
▪ Sound absorber	Integrated
▪ Recirculation	Optional
▪ InTouch function	Standard
▪ Auto stop	▪
▪ Delayed switch off (minutes)	10
▪ Grease filter	6830020
▪ Number of grease filters	2
▪ Grease filter cleaning indication	▪
▪ Recirculation filter cleaning indication	▪
▪ Control method	Remote control
▪ Novy Connect	Standard
▪ Number of speeds	3 + power
▪ Automatic Power revert (minutes)	6

Dimensions

▪ Product dimensions (WxDxH) (mm)	1168 x 508 x 319
▪ Height incl. mounting clamps (without motorbox) (mm)	133
▪ Width flange (mm)	15
▪ Dimensions cut-out opening (WxD) (mm)	1145 x 485
▪ Advised mounting height induction hobs (Hmin-Hmax) (mm)	600 - 1600
▪ Advised mounting height gas hobs (Hmin-Hmax) (mm)	650 - 1600
▪ Advised mounting height ceramic hobs (Hmin-Hmax) (mm)	600 - 1600
▪ Diameter outlet (mm)	150
▪ Position exhaust	Right, Left, Front, Back, Top

Lighting

▪ Functional lighting type	Led strip
▪ Functional light dimmable	▪
▪ Soft-ON/OFF	▪
▪ Total energy consumption functional light (W)	21
▪ Color functional light (K)	2700-5000
▪ Ambient lighting type	Led strip
▪ Total energy consumption ambient light (W)	21
▪ Color ambient light (K)	2700-5000

Airflow and noise level

▪ Free airflow (m ³ /h)	975
▪ Airflow (m ³ /h) measured according to EN 61591	
▪ Sound regulation according to DIN 45635-2	
▪ Airflow duct out speed 1 (m ³ /h) / Max pressure duct out speed 1 (Pa)	262 / 98
▪ Airflow duct out speed 2 (m ³ /h) / Max pressure duct out speed 2 (Pa)	466 / 343
▪ Airflow duct out speed 3 (m ³ /h) / Max pressure duct out speed 3 (Pa)	617 / 391
▪ Airflow duct out max powerspeed (m ³ /h) (Qboost) / Max pressure duct out max powerspeed (Pa)	714 / 391
▪ Sound pressure duct out speed 1 (dB(A)) / Sound power duct out speed 1 (dB(A))	27 / 39
▪ Sound pressure duct out speed 2 (dB(A)) / Sound power duct out speed 2 (dB(A))	40 / 52
▪ Sound pressure duct out speed 3 (dB(A)) / Sound power duct out speed 3 (dB(A))	46 / 59
▪ Sound pressure duct out at max powerspeed (dB(A)) / Sound power duct out at max powerspeed (dB(A)) (LWAboost)	49 / 62

Technical specifications

▪ Maximum power (W)	230
▪ Voltage cooker hood (V)	230
▪ Frequency (Hz)	50
▪ Power consumption in stand-by-mode (Ps) (W)	0,48
▪ Net weight (kg)	22,7
▪ Length power supply cable (m)	1,2

Installation accessories

Dissociated motor

- Dissociated motor
Kit to place motor at distance Pureline with cubic motor $\geq V19$; Pureline Pro with cubic motor $\geq V02$
- 800997

Extension cable

- 7000094 Extension cable 5 m

Novy Sense sensor kit

- 6930060 Kit Novy Sense sensor Pureline Pro

Accessories

Recirculation box



841400

recirculation box with monoblock white (270x500mm)



842400

recirculation box with monoblock (270x500mm)



843400

recirculation box with monoblock grey (270x500mm)




7931400

Recirculation box white with monoblock, H140 mm



7932400

Recirculation box with monoblock, H140 mm



7933400

Recirculation box grey with monoblock, H140 mm

Accessories

**Adapter for limited
installation height**

6930050

Adapter for limited installation height 17,3 cm

