


N 30, Integrated cooker hood, 60 cm, silver  
D61MAC1X0B



COOKING PASSION SINCE 1877



D



The Integrated Cooker Hood with a fold out unit is discreetly hidden within the upper cabinets.

- ✓ LED lighting: a clear illumination whilst cooking thanks to the energy-saving LED lights
- ✓ Reduced Noise: the low-noise motor makes it possible to listen to your own kitchen story

#### Features

##### Technical Data

Typology : Pull-out  
Approval certificates : CE  
Length of electrical supply cord (cm) : 150  
Minimum distance above an electric hob : 500  
Minimum distance above a gas hob : 650  
Net weight (kg) : 11.440  
Type of control : mechanical  
Number of speed settings : 3  
Maximum output air extraction (m<sup>3</sup>/h) : 368  
Number of lights (Stck) : 2  
Noise level (dB(A) re 1 pW) : 62  
Diameter of air outlet (mm) : 150 / 120  
Grease filter material : Washable aluminium  
EAN code : 4242004223351  
Connection rating (W) : 126  
Current (A) : 10  
Voltage (V) : 220-240  
Frequency (Hz) : 50; 60  
Plug type : GB plug  
Installation type : Wall-mounted

#### Optional accessories

Z51IMA0X0 Standard odor filter (replacement)



4 242004 223351

# N 30, Integrated cooker hood, 60 cm, silver

## D61MAC1X0B

### Features

#### Key performance features:

- Energy Efficiency Class: D (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 max. 368 m<sup>3</sup>/h
- Noise max. Normal Level: Noise, max. speed in normal us: 62 dB dB\*

#### Features

- Push button control operation
- 3 power levels
- 2 x 3W LED
- Colour Temperature: 2700 K
- 2 metal grease filter cassettes
- For installation between cupboards

#### Design

- Integrated hood
- Hinged door
- Mechanical controls

#### Performance/technical information

- Suitable for ducted extraction and recirculation
- For recirculated extraction charcoal filter (accessory) needed
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 62 dB(A) re 1 pW
- Power rating: 126 W
- Light Intensity: 188 lux
- Electrical cable length 1.5 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 402-402 x 599 x 271 mm
- Dimensions recirculating (HxWxD): 402-402 x 599 x 271 mm
- Blower Efficiency Class: E\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: C\*
- Average Energy Consumption: 65.7 kWh/year\*

#### Optional accessories

- Recirculating kit Z511MA0X0

\* In accordance with the EU-Regulation No 65/2014