

Type	Technical Code	Commercial Code	Code
Hoods	KF18NLF2XE.50	KT110P1XV	SPP_0004277
<b>General Information</b>			
Stato	HW RnD	Life Cycle	Y2 - On Management
Product Family	HOODS WALLMOUNT 60-120 CM	Aesthetical line	NEUTRAL
Brand	BERTAZZONI	Private Label	BERTAZZONI
Make or Buy Flag	Bought	Type of production	CBU
Type of installation	FREE STANDING	Factory	Guastalla
Technical code	KF18NLF2XE.50	Predecessor Code	KA18NLF2XE.50
Commercial description	110cm Wallmount Hood XV		
Short Description IT	110cm Wallmount Hood XV	Short Description FR	110cm Wallmount Hood XV
Short Description EN	110cm Wallmount Hood XV	Short Description US	110cm Wallmount Hood XV
EAN Required	YES	Ean code	8057971107087
Commercial code	KT110P1XV	Second commercial code	
Market	EUROPE;GREAT BRITAIN	Customer	GENERIC0
Years of warranty		Approvals	CE,UKCA
Notes		Changes notes	
Approval code			
<b>Energy Label</b>			
Energy Label Required	YES	Annual energy consumption - AEOhood (kWh/annum)	73.1
Fluid dynamic efficiency class	B	Fluid dynamic efficiency	25.6
Energy efficiency class	B		
Measured air pressure at best efficiency point - P <sub>beg</sub> (Pa)	395	Minimum air flow in normal use (m <sup>3</sup> /h)	290.0
Maximum air flow in normal use (Intensive / Boost Excluded) (m <sup>3</sup> /h)	590	Air flow at Intensive/Boost Setting - (m <sup>3</sup> /h)	710.0
Lighting efficiency class	A	Light efficiency	109
Power consumption in standby mode - P <sub>s</sub> (W)	0	Power consumption off Mode - P <sub>o</sub> (W)	0.49
Grease filtering efficiency - GFEhood (%)	75.1	Grease filtering efficiency class	C
Energy Label Country	UE + UK		
<b>Technical Data</b>			
Supply voltage [V]/Supply frequency [Hz]	220-240 V , 50/60 HZ	Absorbed power [W]	272
Absorbed current [A]	0	Plug type	NO
Minimum Cable length (m)	1,5	Minimum Cable length (in)	59"
Output air extraction (m <sup>3</sup> /h)	710		
Max extraction power (CFM)	NON APPLICABLE	Max extraction power (SONES)	
Sound level maximum speed (dbA)	65	Sound level maximum speed (Sones)	
Sound level maximum speed/Boost (dbA)	69	Sound level maximum speed/Booster (Sones)	
Sound level minimum speed (dbA)	50	Sound level minimum speed (Sones)	
Microwave magnetron power	NO	Grill max power (W)	NO
Suction type	SUCTION AND FILTER		
<b>Dimensions &amp; Weights</b>			
Size	110		
Height PF (mm)	790	Height PF (in)	31 3/32
Width PF (mm)	998	Width PF (in)	3 15/16
Depth PF (mm)	450	Depth PF (in)	17 23/32
Depth with handle (mm)	0	Depth with handle (in)	0
Depth with open door (mm)	0	Depth with open door (in)	0
Built-in hole height (mm)	0	Built-in hole height (in)	0
Built-in hole width (mm)	0	Built-in hole width (in)	0
Built-in hole depth (mm)	0	Built-in hole depth (in)	0
Chimney height (mm)	730-1000	Chimney height (in)	28 3/4- 39 3/8
Package type	WOOD PALLET		
Package height (mm)	1272	Package height (in)	
Package width (mm)	415	Package width (in)	
Package depth (mm)	603	Package depth (in)	
Hood distance from worktop (mm)	500-650	Hood distance from worktop (in)	19 11/16- 25 19/32
Net weight (Kg)	18.9	Gross weight (Lb)	0.0
Gross weight (Kg)	22.0	Net weight (Lb)	
<b>Aesthetics</b>			
Badge	SERIGRAPHY	Location of fascia	FRONT
Handle type	NO	Knob type	NO
<b>User Interface</b>			
Type of control device	ELECTRIC WITH LED		
Grill power levels	NO	Microwave number of power levels	NO
<b>General Characteristics</b>			
Hood version	WALL MOUNT	Duct cover	INCLUDED
Duct size diameter (in)		Max height of installation (ft)	
Motor	1	Speed	3 + BOOSTER
Filter type	STAINLESS STEEL	Filter cleaning	WASHABLE
Type and number of lights	2 LED		
Filters number	3	Hood Special features	
Perimetal aspiration	NO	Digital airflow control	NO
<b>Microwave</b>			
Microwave type	NO	Microwave functions	NO
Microwave special features	NO	Turntable	NO
Cavity material	NO	Light	NO
Guides type	NO		
Gross volume	0	Net volume	0
Microwave grill tray	NO	Microwave gasket	NO
<b>Safety Devices</b>			
Locked controls	NO	Saturation alarm	NO
<b>Documentation</b>			
Booklet languages	ENGLISH	Warranty certificate	NO
<b>Miscellaneous</b>			
Marketing remarks			