

iQ100, Canopy cooker hood, 53 cm, anthracite LB53NAA30B



D

The powerful canopy cooker hood is concealed in a unit above the hob.

✓ LED lights: For optimal visibility and ambience when cooking.

Features

Technical Data

Typology : Traditional
 Approval certificates : CE
 Length of electrical supply cord (cm) : 150
 Required niche size for installation (HxWxD) : 208mm x 493.0mm x 257mm
 Minimum distance above an electric hob : 550
 Minimum distance above a gas hob : 650
 Net weight (kg) : 4.470
 Type of control : mechanical
 Number of speed settings : 3
 Maximum output air extraction (m3/h) : 302
 Number of lights (Stck) : 2
 Noise level (dB(A) re 1 pW) : 62
 Diameter of air outlet (mm) : 120
 Grease filter material : Washable aluminium
 EAN code : 4242003831717
 Connection rating (W) : 121
 Current (A) : 5
 Voltage (V) : 220-240
 Frequency (Hz) : 50
 Plug type : GB plug
 Installation type : Built-in

Optional accessories

LZ10INT00 Standard recirculation kit
 LZ10INA00 Standard odor filter (replacement)



4 242003 831717

iQ100, Canopy cooker hood, 53 cm, anthracite LB53NAA30B

Features

Key performance features:

- Energy Efficiency Class: D (at a range of energy efficiency classes from A+++ to D)
- Max. extraction rate: 302 m³/h
- Noise max. Normal Level: Noise, max. speed in normal us: 62 dB dB*

Features

- Push button control for extractor speeds and light
- 3 x power levels
- 2 x 3W LED
- Colour Temperature: 2700 K
- 1 x metal grease filter cassette
- For installation in a kitchen cabinet

Design

- Canopy hood
- Mechanical

Performance/technical information

- Suitable for ducted and re-circulating operation
- For recirculated extraction a recirculating kit or a CleanAir recirculation kit (accessory) is needed
- Extraction rate according to EN 61591: max. 302 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 62 dB(A) re 1 pW (48 dB(A) re 20 µPa sound pressure)
- Power rating: 121 W
- Light Intensity: 78 lux
- Electrical cable length 1.5 m
- Diameter pipe Ø 120 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 208-208 x 534 x 300 mm
- Dimensions recirculating, chimney (HxWxD): 208-208 x 534 x 300 mm
- built-in dimensions (HxWxD): 208 x 493 x 257 mm
- Blower Efficiency Class: E*
- Lighting Efficiency Class: D*
- Grease Filtering Efficiency Class: D*
- Average Energy Consumption: 67.7 kWh/year*

Optional accessories

- Recirculating kit LZ10INA00

* In accordance with the EU-Regulation No 65/2014