

LDBI09WSCM3



Colour range

Body



Stainless
steel – SS



Matt
graphite – MG

Finishes

Knobs, handles




Satin



Matt black – D

Configuration

Induction



 Induction zone Ø 160 mm 1,4 kW / 1,1 kW	 Induction zone Ø 160 mm 2,0 kW / 1,4 kW	 Induction zone Ø 215 mm 3 kW / 2,3 kW	 Induction zone Ø 265 mm 3 kW / 2,3 kW
--	--	--	--

<u>Ovens</u>	Primary oven: OV 60 M3		Secondary oven: OV 30 E	
<u>General features</u>	• Energy class A • Operating temperature 30-300°C • Programmer electronic • Electronic temperature control • Lighting double internal light • Full glass oven door • Soft-closing door • Door glass with triple glass (EN60335-2-6-11.101) • High density insulation • Ventilation cooling tangential		• Energy class A • Operating temperature 50-250°C • Lighting internal light • Full glass oven door • Soft-closing door • Door glass with triple glass (EN60335-2-6-11.101) • High density insulation • Ventilation cooling tangential	
<u>Cavity features</u>	• Muffle with easy clean enamel • Internal dimensions (W×H×D) 43,7×34×41 cm • Capacity 65 L • Folding grill heating element • Thermostat with electronic probe		• Muffle with easy clean enamel • Internal dimensions (W×H×D) 27,5×35,5×44 cm • Capacity 43 L • Steam discharge • Rotisserie spit • Thermostat analogue	
<u>Consumptions</u>	• Maximum input 3,2 kW • Top electrical heating element 1000 W • Bottom electrical heating element 1100 W • Electric grill 2100 W • Circular heating element 2100 W		• Maximum input 1,7 kW • Top electrical heating element 800 W • Bottom electrical heating element 800 W • Electric grill 1500 W	
<u>Functions</u>	 Pizza function  Quick start  Multiple fan cooking  Intensive cooking  Fan grill cooking  Grill cooking  Cooking from below  Normal static cooking  ECO cooking		 Grill cooking  Cooking from above  Cooking from below  Normal static cooking	

Technical drawing & dimensions

