| Type | Technical Code | Commercial Code | Code |
|---|---|---|---|
| Hobs | P90R..D2NE.50 | P906IM3G5NE | F004135 |

**General Information**

| | | | | | |
|---|---|---|---|---|---|
| Stato | UnderReview | Life Cycle | Y2 - On Management | | |
| Product family | COOKTOPS 90 CM ELECTRIC | Aesthetical line | NEUTRAL | Colour leading code | BLACK GLASS |
| Brand | BERTAZZONI | Private Label | BERTAZZONI | | |
| Make or Buy Flag | Bought | Type of prodution | CBU | | |
| Type of installation | BUILT IN | Factory | Guastalla | | |
| Technical code | P90R..D2NE.50 | Predecessor Code | | Technical code of derivation | |
| Commercial description | 90 cm Induction hob - 6 Zone | | | | |
| Short Descritpion IT | 90 cm piano induzione, 3 multizone | Short Descritpion FR | Table de cuisson à induction 90 cm - 6 zones | | |
| Short Descritpion EN | 90 cm Induction Hob, 3 multizone | Short Descritpion US | 90 cm Induction hob - 6 Zone | | |
| EAN Required | YES | Ean code | 8054309281440 | | |
| Commercial code | P906IM3G5NE | Second commercial code | | | |
| Market | EUROPE | Customer | GENERICO | | |
| Years of warranty | 2 | | | | |
| Approval code | | Approvals | CE | | |
| Notes | | Changes notes | | | |

**Energy Label**

| | | | |
|---|---|---|---|
| Annual energy consumption - AEChood (kWh/annum) | | Increase factor | |
| Fluid dynamic efficiency - FDEhood (%) | | Energy efficiency index - EEIhood (%) | |
| Fluid dynamic efficiency class | | Energy efficiency class | |
| Measured air flow rate at best efficiency point - Qbep ($m^3$/h) | | Measured electric power input at best efficiency point - Wbep (W) | |
| Air flow at intensive/Boost setting - ($m^3$/h) | | Minimum air flow in normal use ($m^3$/h) | |
| Maximum air flow in normal use (Intensive / Boost excluded) ($m^3$/h) | | Measured air pressure at best efficiency point - Pbep (Pa) | |
| Max air flow ($m^3$/h) | | | |
| Nominal power consumption of the lighting system - Wl (W) | | Average illumination of the lighting system on the cooking surface - Emiddle (Lux) | |
| Light efficiency - LEhood (Lux/Watt) | | Lighting efficiency class | |
| Power consuption in standby mode - Ps (W) | | Power consuption off mode - Po (W) | |
| Grease filtering efficiency - GFEhood (%) | | Grease filtering efficiency class | |
| Sound power level at minimum speed avaible in normal use (dB(A) re 1Pw) | | Sound power level at maximum speed avaible in normal use - (dB(A) re 1Pw) | |
| Sound power level at Intensive/Boost Setting - (dB(A) re 1Pw) | | Odor reduction Factor of (%) | |

**Technical Data**

| | | | |
|---|---|---|---|
| Supply voltage [V]/Supply frequency [Hz] | 230 V , 50 HZ / 60 HZ | Absorbed power [W] | 11100 |
| (Alternative) Supply voltage [V]/Supply frequency [Hz] | | (Alternative) Absorbed power [W] | |
| Absorbed current [A] | 40 | Gas power [kW] | N.A. |
| Electrical supply | Mono 230 V - 40 A | Plug type | NO |
| Minimum Cable length (m) | 1,5 | Minimum Cable length (in) | 59" |
| Gas type | ELECTRIC PRODUCT | Gas connectors | NO |
| Alternative gas | NO | Alternative gas | NO |
| Fan power [W] | N.A. | | |
| Output air extraction ($m^3$/h) | | IEC extraction ($m^3$/h) | |
| Sound level maximum speed (dbA) | | | |

**Dimensions & Weights**

| | | | |
|---|---|---|---|
| Height PF (mm) | 59 | Height PF (in) | |
| Width PF (mm) | 880 | Width PF (in) | |
| Depth PF (mm) | 520 | Depth PF (in) | |
| Built-in hole height (mm) | N.A. | Built-in hole height (in) | |
| Built-in hole width (mm) | 750 | Built-in hole width (in) | |
| Built-in hole depth (mm) | 490 | Built-in hole depth (in) | |
| Package type | STANDARD PACKING | | |
| Package height (mm) | 100 | Package height (in) | |
| Package width (mm) | 1030 | Package width (in) | |
| Package depth (mm) | 625 | Package depth (in) | |
| Net weight (Kg) | 15.0 | Net weight (Lb) | |
| Gross weight (Kg) | 18.5 | Gross weight (Lb) | 0.0 |

**Coordinated Items**

**Aesthetics**

| | | | |
|---|---|---|---|
| Location of fascia | FRONT | Type of lid | NO |
| Knob type | NO | | |

**User Interface**

| | | | |
|---|---|---|---|
| Type of regulation | TOUCH | Cooking programming | END OF COOKING |
| Function indicator | CONTROL PANEL/WORKTOP | | |

**General characteristics**

| | | | |
|---|---|---|---|
| Type of Hob | 90 ELECTRIC GLASS WORKTOP | Power limitation | N.A |
| Information of worktop | GLASS 6 INDUCTION ZONES G5 | Cooking Zone | ELECTRIC |
| Special hob features | AUTO TEMPERATURE SETTINGS;BOOSTER;BRIDGE;CHEF;CHILD LOCK;DOUBLE BOOSTER;EGG TIMER;END OF COOKING;GRILL;KEEP WARM (70°);NEW VALUE;PAUSE/RECALL;RECALL;TIMER | Pan support type | NO |
| Burner and burner cap | NO | Continuous gratings | NO |
| Hob accessories | NO | Type of hood | NO |
| Speed | NO | Filter type | NO |

**Hob layout**

| | | | | | |
|---|---|---|---|---|---|
| No. of total cooking areas | 6 | No. gas burners | | No. of total electric cooking areas | 6 |
| No. electric plates | | No. of radiant areas | 0 | No. halogen areas | 0 |
| No. induction areas | 6 | No. dishwarmer areas | 0 | No. Wok burners | |
| Electric griddle (W) | | | | | |
| No of Power burners | | Power burner - minimum BTU | | Power burner - maximum BTU | |
| No of Rapid burners | | Rapid burner - minimum BTU | | Rapid burner - maximum BTU | |
| No of Medium burners | | Medium burner - minimum BTU | | Medium burner - maximum BTU | |
| No of Simmer burners | | Simmer burner - minimum BTU | | Simmer burner - maximum BTU | |
| No. of bridge induction areas | | Bridge left area - power (W) | | Bridge right area - power (W) | |

**Rear Side**

**Left§Centre§Right**

| | | | | | |
|---|---|---|---|---|---|
| Circular cooking zone or area-diameter surface [mm] zone left-behind | N.A. | Circular cooking zone or area-diameter surface [mm] zone center-behind | N.A. | Circular cooking zone or area-diameter surface [mm] zone right-behind | N.A. |
| Circular cooking zone or area-diameter surface [in] zone left-behind | N.A. | Circular cooking zone or area-diameter surface [in] zone center-behind | N.A. | Circular cooking zone or area-diameter surface [in] zone right-behind | N.A. |
| Non-circula cooking zone or area-lenght [mm] zone left-behind | 210.0 | Non-circula cooking zone or area-lenght [mm] zone center-behind | 210.0 | Non-circula cooking zone or area-lenght [mm] zone right-behind | 210.0 |
| Non-circula cooking zone or area-lenght [in] zone left-behind | | Non-circula cooking zone or area-lenght [in] zone center-behind | | Non-circula cooking zone or area-lenght [in] zone right-behind | |
| Non-circula cooking zone or area-width [mm] zone left-behind | 190.0 | Non-circula cooking zone or area-width [mm] zone center-behind | 190.0 | Non-circula cooking zone or area-width [mm] zone right-behind | 190.0 |
| Non-circula cooking zone or area-width [in] zone left-behind | | Non-circula cooking zone or area-width [in] zone center-behind | | Non-circula cooking zone or area-width [in] zone right-behind | |
| Rear left area - type | INDUCTION | Rear middle area - type | INDUCTION | Rear right area - type | INDUCTION |
| Left rear area - dimensions | 210x190 | Middle rear area - dimensions | 210x190 | Right rear area - dimensions | 210x190 |
| Rear left area - power (W) | 2100 | Rear middle area - power (W) | 2100 | Right rear area - power (W) | 2100 |
| Energy consumption [Wh/Kg] zone left-behind | N.A. | Energy consumption [Wh/Kg] zone center-behind | N.A. | Energy consumption [Wh/Kg] zone right-behind | N.A. |
| Energy efficiency per gas burners [%] zone left-behind | N.A. | Energy efficiency per gas burners [%] zone center-behind | N.A. | Energy efficiency per gas burners [%] zone right-behind | N.A. |
| Rear left area - power booster [W] | 2600 | Rear middle area - power booster [W] | 2600 | Rear right area - power booster [W] | 2600 |
| Rear left area - double power booster [W] | 3700 | Rear middle area - double power booster [W] | 3700 | Rear right area - double power booster [W] | 3700 |

**Middle Side**

**Left§Centre§Right**

**Front Side**

**Left§Centre§Right**

| | | | | | |
|---|---|---|---|---|---|
| Circular cooking zone or area-diameter surface [mm] zone left-ahead | N.A. | Circular cooking zone or area-diameter surface [mm] zone center-ahead | N.A. | Circular cooking zone or area-diameter surface [mm] zone right-ahead | N.A. |
| Circular cooking zone or area-diameter surface [in] zone left-ahead | N.A. | Circular cooking zone or area-diameter surface [in] zone center-ahead | N.A. | Circular cooking zone or area-diameter surface [in] zone right-ahead | N.A. |
| Non-circula cooking zone or area-lenght [mm] zone left-ahead | 210.0 | Non-circula cooking zone or area-lenght [mm] zone center-ahead | 210.0 | Non-circula cooking zone or area-lenght [mm] zone right-ahead | 210.0 |
| Non-circula cooking zone or area-lenght [in] zone left-ahead | | Non-circula cooking zone or area-lenght [in] zone center-ahead | | Non-circula cooking zone or area-lenght [in] zone right-ahead | |
| Non-circula cooking zone or area-width [mm] zone left-ahead | 190.0 | Non-circula cooking zone or area-width [mm] zone center-ahead | 190.0 | Non-circula cooking zone or area-width [mm] zone right-ahead | 190.0 |
| Non-circula cooking zone or area-width [in] zone left-ahead | | Non-circula cooking zone or area-width [in] zone center-ahead | | Non-circula cooking zone or area-width [in] zone right-ahead | |
| Left front area - type | INDUCTION | Middle front area - type | INDUCTION | Front right area - type | INDUCTION |
| Left front area - dimensions | 210x190 | Middle front area - dimensions | 210x190 | Right front area - dimensions | 210x190 |
| Front left area - power (W) | 2100 | Middle front area - power (W) | 2100 | Front right area - power (W) | 2100 |
| Energy consumption [Wh/Kg] zone left-ahead | N.A. | Energy consumption [Wh/Kg] zone center-ahead | N.A. | Energy consumption [Wh/Kg] zone right-ahead | N.A. |
| Energy efficiency per gas burners [%] zone left-ahead | N.A. | Energy efficiency per gas burners [%] zone center-ahead | N.A. | Energy efficiency per gas burners [%] zone right-ahead | N.A. |
| Front left area - power booster [W] | 2600 | Front middle area - power booster [W] | 2600 | Front right area - power booster [W] | 2600 |
| Front left area - double power booster [W] | 3700 | Front middle area - double power booster [W] | 3700 | Front right area - double power booster [W] | 3700 |

**Safety devices**

| | | | |
|---|---|---|---|
| Hob ignition | TOUCH CONTROL | Hob flame failure device | NO |
| Locked controls | YES | Residual heat indicators | YES |
| Overflow security | YES | | |

**Documentation**

| | | | |
|---|---|---|---|
| Booklet languages | ENGLISH;FRENCH;ITALIAN;SPANISH;SPANISH (MEXICO) | Warranty certificate | NO |

**Miscellaneous**

| | |
|---|---|
| Special features hoods | NO |

**Hob with hood**

| | | | | |
|---|---|---|---|---|
| Max extraction power (CFM) | | Suction type | | |
| Sound level maximum speed/Boost (dbA) | | Sound level minimum speed (dbA) | | |
| Sound level maximum speed (Sones) | | Sound level maximum speed/Booster (Sones) | | Sound level minimum speed (Sones) |