


*N 70, GAS HOB, 90 CM, STAINLESS STEEL
T29CIR8N0*



The gas hob with precise flame control, removable dials and pan supports that are suitable for dishwashers - for Comfort Clean.

- ✓ FlameSelect®: Gain precise control of your flame.
- ✓ Metallic Sword Dial: Precise and removable for easy cleaning.
- ✓ Cast Iron Pan Supports: For maximum stability and dishwasher cleaning.
- ✓ Dual Wok Burner up to 5.0 kW: Use one gas flame for simmering, two for sizzling stir-fries.
- ✓ Gas Safety Cut-Off: Safety first! No flame, no gas flow.

Optional accessories

Z1365WX0	Wireless food thermometer
Z2402X0	Small pot support
Z2471X0	Wok ring
Z2480X0	Simmer plate
Z9404SE0	4 pieces Set
Z9406SE0	6 pieces Set

Features

Technical Data

Product name/family:gas hob w
integrated controls
Built-in / Free-standing: Built-in
Energy input: Gas
Number of cooking zones: 5
Required niche size for installation (HxWxD): 45 x 850-850 x
490-500 mm
Width of the appliance: 915 mm
Dimensions: 51.5x915x520 mm
Dimensions of the packed product (HxWxD): 165 x 1116 x 659
mm
Net weight: 16.0 kg
Gross weight: 18.6 kg
Residual heat indicator: Separate
Location of control panel: Front
Basic surface material: Stainless steel
Color of surface: Stainless steel
Length electrical supply cord: 100.0 cm
EAN code: 4242004284666
Gas connection rating: 12500 W
Fuse protection: 3 A
Voltage: 220-240 V
Frequency: 50; 60 Hz



N 70, GAS HOB, 90 CM, STAINLESS STEEL T29CIR8N0

Features

Design

- Stainless steel surface
- black cast iron pan supports with protective rubber feet
- full metal

Usage convenience

- FlameSelect with 9 steps: precisely control and adjust the flame in nine defined levels.
- Design co-ordinated control dials, front: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

Burners and power

- 5 burner hob
- Including 1 wok burner: use an extra wide power range, separately controlling two flame rings.
- Left front: Economy burner up to 1 KW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Center front: Wok burner up to 5 KW (depending on gas type)
- Right rear: High speed burner up to 3 KW (depending on gas type)
- Right front: Standard burner up to 1.75 KW (depending on gas type)

Cleaning

- Removable control dials for easy cleaning between knobs.
- Dishwasher suitable pan supports for easy cleaning.

Safety

- Flame failure safety device: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE)
- NG H/E 20mbar, E+ 20/25mbar Natural gas H 25 mbar (HU) Natural gas L 25 mbar (NL) Liquid gas G30,31 28-30/37mbar Liquid gas G30 37 mbar (PL) Liquid gas 50 mbar
- Factory set for connection to mains gas
- Nozzle set for LPG jets (28-30/37mbar) included. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): 51.5 x 915 x 520
- Required niche size for installation (HxWxD mm) : 45 x 850 x (490 - 500)
- Min. worktop thickness: 20 mm
- Power cord: 1 m
- Connected load: 12.5 KW

Accessories

- 1 x WOK attachment ring included

