

N 90, GAS HOB, 90 CM, TEMPERED GLASS, BLACK  
T29RHS4S0



The gas hob with precise flame control, an easy-to-clean surface and smart hob-hood-interaction.

- ✓ FlameSelect®: Gain precise control of your flame.
- ✓ Illuminated Metallic Sword Dial: Bright, precise and removable for easy cleaning.
- ✓ Cast Iron Pan Supports: Maximum stability, easy handling, and dishwasher cleaning.
- ✓ Touch Control Display: Set a timer or control your hood.
- ✓ Hob-Hood Control: Convenient hood operation via your hob.

Optional accessories

Z1365WX0	Wireless food thermometer
Z2402X0	Small pot support
Z2471X0	Wok ring
Z2480X0	Simmer plate
Z9404SE0	4 pieces Set
Z9406SE0	6 pieces Set

Features

Technical Data

Product name/family:	.....gas hob w integrated controls
Built-in / Free-standing:	..... Built-in
Energy input:	..... Gas
Number of cooking zones:	..... 5
Required niche size for installation (HxWxD):	..... 45 x 850-850 x 490-500 mm
Width of the appliance:	..... 915 mm
Dimensions:	..... 54x915x520 mm
Dimensions of the packed product (HxWxD):	..... 165 x 1116 x 659 mm
Net weight:	..... 21.3 kg
Gross weight:	..... 24.7 kg
Residual heat indicator:	..... Separate
Location of control panel:	..... Front
Basic surface material:	..... Tempered glass
Color of surface:	..... Black
Color of frame:	..... Black
Length electrical supply cord:	..... 100.0 cm
EAN code:	..... 4242004284673
Gas connection rating:	..... 13700 W
Fuse protection:	..... 3 A
Voltage:	..... 220-240 V
Frequency:	..... 50; 60 Hz



## N 90, GAS HOB, 90 CM, TEMPERED GLASS, BLACK T29RHS4S0

### Features

#### Design

- tempered glass surface, black
- Cast iron pan supports with rubber feet
- illuminated full metal

#### Usage convenience

- FlameSelect with 9 steps: precisely control and adjust the flame in nine defined levels.
- LED display for each zone: see the selected power level and the residual heat.
- Design co-ordinated control dials, front: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.
- LED timer for each zone with switch off function and acoustic signal: an alarm sounds at the end of the time set (e.g. for pasta).

#### Burners and power

- 5 burner hob
- Including 1 wok burner: use an extra wide power range, separately controlling two flame rings.
- Left: Wok burner up to 5 KW (depending on gas type)
- Center front: Standard burner up to 1.75 KW (depending on gas type)
- Center rear: standard burner up to 1.75 KW (depending on gas type)
- Right rear: High speed burner up to 3 KW (depending on gas type)
- Right front: Economy burner up to 1 KW (depending on gas type)

#### Cleaning

- Removable control dials for easy cleaning between knobs.
- Dishwasher suitable pan supports for easy cleaning.
- Cast iron pan supports with rubber feet: little weight and compact form, yet high stability due to continuous surface.

#### Safety

- Flame failure safety device: prevents unwanted gas flow when flame goes out.
- 1 stage: indicates which burner parts and pan supports are still hot.

#### Connectivity

- Home Connect : check if the hob is switched off even when not at home and find additional functions in the Home Connect app.
- Hob Hood Control - hood control (with Wi-Fi enabled hood) : automatically activates the hood when cooking, thanks to the WiFi connection of hob and suitable hood.
- Smart Hood Automatic: hood automatically adapts fan speed thanks to hob continuously providing cooking data (with matching hood and connected Home Connect account).
- Sound volume of touch control adaptable to personal preference and needs (via app).

#### Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE)
- NG H/E 20mbar, E+ 20/25mbar Natural gas H 25 mbar (HU) Natural gas L 25 mbar (NL) Liquid gas G30,31 28-30/37mbar Liquid gas G30 37 mbar (PL) Liquid gas 50 mbar

- Factory set for connection to mains gas
- Nozzle set for LPG jets (28-30/37mbar) included. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): 54 x 915 x 520
- Required niche size for installation (HxWxD mm) : 45 x 850 x (490 - 500)
- Min. worktop thickness: 20 mm
- Power cord: 1 m
- Connected load: 13.7 KW

#### Accessories

- 1 x WOK attachment ring included

N 90, GAS HOB, 90 CM, TEMPERED GLASS, BLACK  
T29RHS4S0

Dimensioned drawings

